Cheatography

Golang Cheat Sheet

by [deleted] via cheatography.com/23330/cs/5127/

Basic Syntax

```
package main
import " fmt "
func main() {
        fmt.Pr int ln( " Hello
Go")
}
```

Packages

- package declaration at top of every source file
- executables are in package main
- convention: package name == last name of import path (import path math/rand => package rand)
- upper case identifier: exported (visible from other packages)
- Lower case identifier: private (not visible from other packages)

Operators

Arithmetic

```
+ addition
- subtra ction
* multip lic ation
/ quotient
% remainder
& bitwise and
| bitwise or
^ bitwise xor
&^ bit clear (and not)
<< left shift
>> right shift
```

Comparison

```
== equal
!= not equal
< less than
<= less than or equal
> greater than
>= greater than or equal
```

Operators (cont)

> Logical

&& logical and

|| logical or

! logical not

Other

& address of / create pointer

* dereference pointer

<- send / receive operator

Functions

```
// a simple function
func functi onN ame() {}
// function with parameters
func functi onN ame (param1
string, param2 int) {}
// multiple parameters of the
same type
func functi onN ame (pa ram1,
param2 int) {}
// return type declar ation
func functi onN ame() int {
        return 42
}
// return multiple
func return Multi() (int,
string) {
        return 42, " foo bar "
}
var x, str = return Multi()
// Return multiple named results
simply by return
func return Mul ti2() (n int, s
string) {
       n = 42
       s = " foo bar "
       // n and s will be
returned
        return
}
var x, str = return Mul ti2()
```

Functions As Values And Closures

```
func main() {
       // assign a function to a
name
>     add := func(a, b int) int {
       return a + b
    }
    // use the name to call the function
    fmt.Println(add(3, 4))
}
// Closures, lexically scoped: Functions can
access values that were
// in scope when defining the function
func scope() func() int{
    outer_var := 2
    foo := func() int { return outer_var}
    return foo
}
func another_scope() func() int{
    // won't compile because outer_var and
foo not defined in this scope
    outer_var = 444
    return foo
}
// Closures: don't mutate outer vars, instead
redefine them!
func outer() (func() int, int) {
    outer_var := 2
    inner := func() int {
        outer_var += 99 // attempt to mutate
outer_var from outer scope
        return outer_var // => 101 (but
outer_var is a newly redefined
                    // variable visible only inside
inner)
    }
    return inner, outer_var // => 101, 2
(outer_var is still 2, not mutated by foo!)
}
```

Variadic Functions

Sponsored by CrosswordCheats.com
Learn to solve cryptic crosswords!
http://crosswordcheats.com

Functions (cont)

```
> func main() {
    fmt.Println(adder(1, 2, 3)) // 6
    fmt.Println(adder(9, 9)) // 18
    nums := []int{10, 20, 30}
    fmt.Println(adder(nums...)) // 60
}
// By using ... before the type name of the last parameter you can indicate that it takes zero or more of those parameters.
// The function is invoked like any other function except we can pass as many arguments as we want.
func adder(args ...int) int {
    total := 0
    for _, v := range args { // Iterates over the arguments whatever the number.
        total += v
    }
    return total
}
```

Declarations

```
var foo int // declaration without initial.
var foo int = 42 // declar ation with initial
var foo, bar int = 42, 1302 // declare and init
var foo = 42 // type omitted, will be inferred
foo := 42 // shorthand
const constant = "This is a consta nt"
```

Type Conversions

```
var i int = 42
var f float64 = float64(i)
var u uint = uint(f)
// altern ative syntax
i := 42
f := float64(i)
u := uint(f)
```

Arrays, Slices, Ranges

Arrays

```
var a [10]int
// declare an int array with length 10. Array length is part of the type!
a[3] = 42 // set elements
i := a[3] // read elements
// declare and initialize
var a = [2]int{1, 2}
a := [2]int{1, 2} //shor thand
a := [...]i nt{1, 2} // elipsis -> Compiler figures out array length
```

Slices

```
var a []int // declare a slice - similar to an array, but length is unspec ified
var a = []int {1, 2, 3, 4} // declare and initialize a slice (backed by the array given implic itly)
a := []int{1, 2, 3, 4} // shorthand
chars := []stri ng{ 0:"a ", 2:"c ", 1: " b"} // ["a", " b", " c"]
var b = a[lo:hi] // creates a slice (view of the array) from index lo to hi-1
var b = a[1:4] // slice from index 1 to 3
var b = a[:3] // missing low index implies 0
var b = a[3:] // missing high index implies len(a)
// create a slice with make
a = make([ ]byte, 5, 5) // first arg length, second capacity
a = make([ ]byte, 5) // capacity is optional
// create a slice from an array
x := [3]str ing {"Ла йка ", " - Бел ка", " Стр елк а"}
```

Arrays, Slices, Ranges (cont)

```
> s := x[:] // a slice referencing the storage of x
```

Built-in Types

```
bool
string
int int8 int16 int32 int64
uint uint8 uint16 uint32 uint64
uintptr
byte // alias for uint8
rune // alias for int32 ~= a character (Unicode code point) - very Viking
float32 float64
complex64 complex128
```

Control structures

If

```
func main() {
        // Basic one
        if x > 0 {
                return x
        } else {
                return -x
        }
        // You can put one statement before the condition
        if a := b + c; a < 42 {
                return a
        } else {
                return a - 42
        }
        // Type assertion inside if
        var val interf ace{}
        val = " foo "
        if str, ok := val.(s - tring); ok {
                fmt.Pr int - ln(str)
        }
}
```

Loops

Sponsored by CrosswordCheats.com
Learn to solve cryptic crosswords!
http://crosswordcheats.com

Control structures (cont)

```
> // There only for, no while, no until
    for i := 1; i < 10; i++ {
    }
    for ; i < 10; { // while - loop
    }
    for i < 10 { // omit semicolons
    }
    for { //omit the condition ~ while (true)
    }
```

Switch

```
    switch operatingSystem {
    case "darwin":
        fmt.Println("Mac OS Hipster")
        // cases break automatically
    case "linux":
        fmt.Println("Linux Geek")
    default:
        // Windows, BSD, ...
        fmt.Println("Other")
    }
    // as with for and if, you can have an
assignment statement before the switch
value
    switch os := runtime.GOOS; os {
    case "darwin": ...
    }
```


Sponsored by **CrosswordCheats.com**
Learn to solve cryptic crosswords!
http://crosswordcheats.com